



## Inside This Issue:

### Bends, Doesn't Break

Interaction between materials is a crucial piece of the bendable concrete puzzle.



### Used Around the World

ECC is used in building and infrastructure projects in several countries.



### First Application in U.S.

MDOT uses ECC on bridge in Ypsilanti, becomes first in U.S. to use it on transportation infrastructure



### New Challenges, New Opportunities

Unexpected cracking makes clear the need for holistic approach to design.



### Inherently Sustainable

Use of waste materials, low environmental impact and low life cycle costs highlight the sustainable nature of ECC.



### Future Becoming Clearer

Research continues to improve our understanding and refine our implementation of new materials.

# Bendable Concrete Provides Insight into Sustainable Material Development Process

Materials that work together and interact with each other is the essence of a sustainable system.

A hush falls over the crowd as one of the greatest golfers of all time stoops to place his ball on the tee. The summer sun is high in the mid-afternoon sky as he straightens and squints down the perfectly manicured, lush, green fairway. Gripping his club with the practiced hands of a surgeon holding a scalpel, he assumes a stance, relaxed but purposeful, with his feet in line with the ball's intended path of travel.

With an almost imperceptible intake of breath, he begins his backswing, his shoulders and hips rotating as he brings the club back, back, back. Then his swing begins. His body, coiled like a tightly-wound spring, explodes at

just the right moment to generate 130 mph club-head speed, which (with a satisfying CRACK) sends the ball over 300 yards straight down the fairway. With the ball still rolling after it lands, he stoops to pick up his tee. Handing the club and tee to his caddy, he acknowledges the roar of the gallery with a glance and a wave.

Tiger Woods' golf swing is beautiful, and you don't have to be a golf enthusiast to appreciate it. It's smooth and elegant but also powerful and intense. The speed of his club

head as it comes into contact with the ball is among the highest of all pro golfers. But anyone who has chased the venerable dimpled sphere around a golf course knows that club head speed is only a small part of the game. Without the proper grip and stance and hip and shoulder rotation, and timing, and even emotional state, club head speed could determine how deep in the woods someone will someday find your ball.

**"ECC is a carefully engineered system. Every component is specifically designed to work with the others to achieve desired performance characteristics"**

Dr. Victor C. Li., Director, U-M Advanced Civil Engineering Materials Research Laboratory

An effective golf swing is a precise combination of actions that work together to send a ball a desired distance in a predictable direction.

Engineered Cementitious Composites (ECC), under development at the University of Michigan's (U-M) Advanced Civil Engineer-

ing Materials Research Laboratory (ACE MRL) since 1992 (the same year Tiger competed in his first PGA Tour event), are similar to a great golf swing. And you don't have to be an engineer to appreciate them. ECC, or bendable concrete, is made up of a precise combination of materials that work together to achieve a desired strength and predictable flexibility. ECC was discovered by Victor C. Li, Director of ACE MRL, who applied principles of microstructure tailoring to precisely control the interaction between the different materials that make up ECC. Micro-

structure tailoring describes the process of predicting the properties and characteristics of combinations of materials based on known properties of the individual materials before combining them. “ECC is a carefully engineered system,” Li explains. “Every component is specifically designed to work with the others to achieve desired performance characteristics.” The key performance characteristics exhibited by ECC include: extreme flexibility, high fatigue resistance, very low fluid permeability, and compressive strength similar to that of ordinary concrete and fiber reinforced concrete (FRC).

### Bends Without Breaking

ECC flexes without fracturing due to the interaction between fibers, sand, and cement working in a matrix that binds everything together within the material. “In addition to reinforcing the concrete with fibers that act as ligaments to bond it more tightly,” Li explains, “we design the cement matrix with special ingredients to make it more compatible with the fibers and to increase flexibility.”

Where ordinary concrete and FRC are designed to resist cracking, ECC is designed to crack only in a carefully controlled manner. The cracks that appear in ordinary concrete and FRC are Griffith-type cracks; they increase in width as they grow longer. The cracks that are designed into ECC are steady state (or flat) cracks; the width of these cracks remains constant regardless of the length. “Through microstructure tailoring, we’re able to design ECC with a combination of materials such that the capacity of the fibers that bridge the cracks is greater than the capacity of the matrix to resist cracking, Li explains. U-M holds several patents on ECC technologies.

### Used Around the World

The unique ability of ECC to bend while maintaining physical properties similar to other types of concrete has led to its use in a variety of new vertical and horizontal construction applications in Japan, Korea, Switzerland, Australia and the United States. For example, the Mihara Bridge in Hokkaido, Japan, open to traffic in May, 2005, uses a composite deck made of steel and ECC. This bridge is 40% lighter than a bridge that uses a conventional design, and the expected service life of the deck is 100 years.

### First Application in the U.S.

MDOT initiated the first use of ECC in a transportation infrastructure project in the U.S. in 2005. The Grove Street Bridge over I-95 in Ypsilanti uses steel concrete girders supported at piers. The girders support cast-in-place concrete decks. A mechanical expansion joint was originally used between these simple decks to allow for deck deformations imposed by deflection, concrete shrinkage, and temperature variations. Over time,

deterioration of joint performance allowed water and deicing chemicals to leak through the joint and over the substructure, and ultimately resulted in severe damage to the bridge deck and substructure (see Figure 1-A).

Reconstruction of the bridge, completed in December 2005, incorporated an ECC link slab instead of a traditional mechanical joint between deck slabs (see Figure 2-B). “This demonstration project fit well with the Department’s strategic research plan,” Calvin Roberts, Administrator of MDOT’s Office of Research and National Best Practices explains. “Improving bridge joints and increasing the life of bridge decks are two key objectives in the plan.” Technical details of the project were summarized in Issue 100 of the *MDOT C&T Research Record* (August 2005).

Link slabs have been in use since the 1930s, and their advantage over mechanical joints was verified and documented through research conducted by Alampalli and Yannotti (1998). Unlike a conventional joint, which requires a great deal of maintenance and is susceptible to debris buildup and water infiltration, a link slab is virtually maintenance free and provides a debris- and water-tight seal. Research to determine the durability of link slabs, conducted by Caner and Zia (1998), showed that they are subjected to bending loads under traffic conditions and as a result, tensile cracks develop at the tops of the slabs. These tensile cracks expand to allow water infiltration to the reinforcing steel, which leads to corrosion and further deterioration. Caner and Zia also concluded that additional tensile stress may be imposed on link slabs due to shrinkage, creep, and temperature loading.

### ECC Capabilities for Link Slabs Documented

Prior to the Grove Street Bridge project, an experimental study funded by MDOT and conducted by Kim, Fischer, and Li (2003) showed that ECC was capable of withstanding the forces exerted on a link slab. Of particular note in this study was the comparison of crack widths between link slabs made with ordinary concrete and those made with ECC. After 100,000 loading cycles in the lab, crack widths in the concrete link slab were approximately 640  $\mu\text{m}$  wide. Under the same loading conditions, crack widths in the ECC link slab were less than 50  $\mu\text{m}$  wide, which is about  $\frac{1}{4}$  the width of a human hair.

### Unexpected Cracking

Three days after placement on the Grove Street Bridge, early age cracking was found in the link slab. After one year of normal traffic and environmental loading, crack widths were 0.006 in. to 0.01 in., still smaller than the AASHTO standard of 0.013 in. after one year, but larger than they should have been. “Fewer cracks developed than expected and the cracks are wider than anticipated,” said Roger Till, MDOT Project Manager. “We have initiated a follow-up project to resolve the cracking issue.”



**Figure 1. Slab and Support on Grove Street Bridge in Ypsilanti, Michigan, Before and After Reconstruction.**

This follow up project, which is an extension of the initial project and is expected to be completed in January 2008, identifies potential causes of the cracking. Nearly all have something to do with the interaction between the ECC link slab, the structural components of the bridge, and the environment. The project sets forth a plan to replicate the cracking to understand it better, and also take steps to prevent it from happening in future applications.

#### **Exciting Possibilities for Sustainable Applications**

Michael Lepech, research fellow at the University of Michigan's Center for Sustainable Systems, and a co-author of the ECC link slab project, is keenly interested in this process of ex-

perimentation that requires a holistic approach to development. "It comes down to sustainability," Lepech explains. "A sustainable system is one that takes all components into consideration and creates cooperation and synergy among them."

ECC is an exciting material for those interested in sustainability. The very process of designing ECC, for example, lends itself to experimentation with recycled, reclaimed, and waste materials. "Our growing understanding of the interaction between fibers, sand, and cement within ECC enables us to precisely adjust any of the elements to accommodate variations in the others," Lepech explains. An experimental version of ECC that uses a combination of cement kiln dust and green foundry sand to replace some or all of the ordinary cement and sand

actually performed better than a version that used the ordinary materials. Cement kiln dust is a by-product of the portland cement production process. Green foundry sand is a by-product of the metal casting process. Both materials are produced in large quantities in Michigan, and both have historically been disposed of in landfills.

“It’s great to be able to put these otherwise useless and even environmentally damaging materials to use like this,” Lepech says. “We’re constantly on the look out for new materials to try in ECC.”

**Lower Environmental Impact, Less Expensive Over Time**

The results of a study conducted by Keoleian, Kendall, Lepech, and Li (2006) provide another indication that ECC could play a key role as a material in sustainable transportation infrastructure applications. This study used life cycle modeling techniques to compare the sustainability performance of a bridge that uses traditional steel expansion joints to that of a bridge that uses ECC link slabs.

Life cycle modeling is completed in two parts. The first involves performing a life cycle assessment, which provides a measure of environmental and social impacts of using a product, system or technology. The second part is a life cycle cost analysis, which uses life cycle assessment data to calculate costs from various perspectives.

The study showed that bridge decks with ECC link slabs are less impactful on the environment and cost less over a 60 year service life than those using steel expansion joints (see Table 1).

Bearer of Cost	Steel Expansion Joint	ECC Link Slab	ECC Cost Advantage
Agency	\$ 640,000	\$ 500,000	22%
User	\$ 21,300,000	\$18,200,000	14%
Environment	\$ 34,000	\$ 26,000	22%
Total	\$ 22,000,000	\$ 19,000,000	15%

**Table 1. Total Life Cycle Costs.**

**Research is Improving Clarity**

When describing the process of discovery that is playing out in the area of sustainable transportation infrastructure today, Dr. Lepech uses an analogy from a book, *Educating the Reflective Practitioner* (1987). The book was written by the late Dr. Donald Schön, a renowned organizational development expert and

Professor of Philosophy at MIT. “In the varied topography of professional practice, there is a high, hard ground overlooking a swamp,” Schön writes. “On the high ground, manageable problems lend themselves to solution through the application of research-based theory and technique. In the swampy lowland, messy, confusing problems defy technical solution.” In the book, Schön goes on to describe how problems often present themselves not as well-formed structures, but rather as “messy, indeterminate situations.”

Today the work of researchers in the “swampy lowlands” is filtering the previously murky water. As a result, we’re beginning see relationships more clearly, and we’re beginning to understand for the first time how links between “high and hard” islands of understanding can provide exciting and fascinating solutions to problems that up until now seemed unsolvable. Like a 300 yard drive straight down the fairway, each of these solutions requires a combination of actions strung together in precisely the right way. And the results are smooth and elegant, powerful and intense; beautiful to see. And you don’t have to be an engineer to appreciate them.

**References**

McNinch, T., J. Rynanen, M. B. Larson, 2005, *Bridge Decks Going Jointless*. MDOT C&T Research Record 100.

Alampalli, S. and A.P. Yannotti, 1998, *In-Service Performance of Integral Bridges and Jointless Decks*. Transportation Research Record 1624, Paper No. 98-0540.

Caner, A. and P. Zia, 1998, *Behavior and Design of Link Slab for Jointless Bridge Decks*. PCI J., May-June, pp.68-80.

Li, V.C. and M. Lepech, 2004, *Field Demonstration of Durable Link Slabs for Jointless Bridge Decks Based on Strain-Hardening Cementitious Composites*. MDOT Research Report RC- 1471.

Keoleian, G.A., A.M. Kendall, M.D. Lepeck, V.C. Li, 2006, *Guiding the design and application of new materials for enhancing sustainability performance: Framework and infrastructure application*. Mater. Res. Symp. Proc. Vol. 895.

Schön, D. A., 1987, *Educating the Reflective Practitioner*. San Francisco, CA, London, England.

© 2007 Michigan Technological University. To obtain permission to reprint text or graphics from this publication, or if you have suggestions or questions, contact Calvin Roberts, Administrator, MDOT Office of Research and National Best Practices; 517-241-4667, FAX 517-355-2785.

Produced by:



Michigan's  
Local Technical  
Assistance Program

John Rynanen, Editor